



DA Series  
**Single and Multi-Tenant  
Entry Security System**



**Residential and Commercial Applications**

## Features and Benefits

### Access control

Provide entry security for up to four tenants sharing a common entrance.

### Visitor screening

Safely and conveniently speak with visitors to determine their intent before unlocking the door.

### Replaces doorbell, easy to install

Reduce installation costs by using existing doorbell wire. No doorbell? *No problem!* The system only requires two wires, making installation a snap!

### Door release

**powered by system**  
Have the convenience of door release without needing to purchase additional power.

### Simple to use

Answer calls and unlock the entrance with simple, intuitive operation.

### Reliable and designed to last

Enjoy trouble-free use for years to come, even after the warranty expires!



## Components

**Box Set** (select if DA-1DS is the desired entrance station— for 1x1 applications only)



**DA-1AS**  
Single Tenant Box Set (includes one DA-1DS door station, one DA-1MD master station, and one PT-1211CA power supply)

**Entrance Stations: select 1**  
(for a la carte applications)



**DA-1DS**  
1-Call Audio Entrance Station (included with DA-1AS box set)



**DA-2DS**  
2-Call Audio Entrance Station



**DA-4DS**  
4-Call Audio Entrance Station

- Weather resistant
- Direct select button(s)
- Backlit directory
- Connects to door strike
- Hands-free communication
- Surface mount

6-7/8" H 3-15/16" W 7/8" D

**Master Station: select up to 4**



**DA-1MD**  
Audio Tenant Station with Handset (included with DA-1AS box set)  
7-7/8" H 3-1/2" W 2-1/2" D

### Accessories

**EL-12S**  
Electric Door Strike for Wood Frames  
4-1/8" H 13/16" W 1-1/8" D

### Power Supply



**PT-1211CA**  
15V AC Transformer (included with DA-1AS box set)  
3-1/16" H 2-3/8" W 1-7/8" D

## Specifications

<b>Power Source</b>	15V AC—use PT-1211CA	<b>Communication</b>	Handset (full duplex)
<b>Door Release</b>	9.5–20V AC, 70Ω or higher resistance—use EL-12S		
<b>Wire Type</b>	Entrance Station to Tenant Station: 2-cond., overall shield—use Aiphone #822202 or 2-cond., low cap, PE insulation, solid, non-shielded—use Aiphone #871802 Power Supply to Tenant Station: 2-cond., low cap, PE insulation, solid, non-shielded—use Aiphone #871802		
<b>Distance</b>	Power Supply to Entrance Station or Door Strike (cumulative): 360' (22 AWG) 1,020' (18 AWG) Power Supply to Tenant Station: 180' (22 AWG) 510' (18 AWG)		

**Combine this intercom system with our AC Series access control solution for more security benefits!**



**AIPHONE**  
SECURITY  
COMMUNICATION  
SOLUTIONS  
aiphone.com

**Customer Service  
and Technical Support**  
**(800) 692-0200**

Headquarters – Redmond, WA  
East Office – Cherry Hill, NJ  
Canada Office – Laval, QC

WATCH | CONNECT | LIKE | FOLLOW



DA Series Brochure

© 2023 Aiphone Corp.  
Revised 08/2023.  
All rights reserved.  
Designed in the USA.

The information in this brochure is subject to change without notice.