



DB Series
**Single and Multi-Tenant
Entry Security System**



Residential and Commercial Applications

Components

Superior audio system

Replace existing audio systems with less wires and a larger capacity.

Access control

Provide entry security for up to four tenants sharing a common entrance.

Visitor screening

Safely and conveniently speak with visitors to determine their intent before unlocking the door.

Replaces doorbell, easy to install

Reduce installation costs by using existing doorbell wire. No doorbell? *No problem!* The system only requires two wires, making installation a snap!

Door release powered by system

Have the convenience of door release without needing to purchase additional power.

Simple to use

Answer calls and unlock the entrance with simple, intuitive operation.

Reliable and designed to last

Enjoy trouble-free use for years to come, even after the warranty expires!

Internal communication

Install up to four tenant sub stations per tenant master station to speak with hands-free or push-to-talk communication using the All Call feature.



Box Set (select if DA-1DS is the desired entrance station— for 1x1 applications only)



DBS-1A

Single Tenant Box Set (includes one DA-1DS door station, one DB-1MD master station, and one PT-1211CA power supply)

Entrance Stations: select 1 (for a la carte applications)



DA-1DS

1-Call Audio Entrance Station (included with DA-1AS box set)

- Weather resistant
- Direct select button(s)
- Backlit directory
- Connects to door strike
- Hands-free communication
- Surface mount

6-7/8" H 3-15/16" W 7/8" D



DA-2DS

2-Call Audio Entrance Station

- Weather resistant
- Direct select button(s)
- Backlit directory
- Connects to door strike
- Hands-free communication
- Surface mount

6-7/8" H 3-15/16" W 7/8" D



DA-4DS

4-Call Audio Entrance Station

- Weather resistant
- Direct select button(s)
- Backlit directory
- Connects to door strike
- Hands-free communication
- Surface mount

6-7/8" H 3-15/16" W 7/8" D

Tenant Master Station: select up to 4



DB-1MD

Audio Tenant Master Station (included with DBS-1A box set)

7-5/16" H

3-1/8" W

1-1/16" D

Tenant Sub Station: select up to 4 per tenant master station (optional)

DB-1SD

Audio Tenant Sub Station

7-5/16" H

3-1/8" W

1-1/16" D



Components

Power Supply



PT-1211CA

15V AC Transformer
(included with DA-1AS
box set—one required
per two DB-1SDs)
3-1/16" H
2-3/8" W
1-7/8" D

Accessories



EL-12S

Electric Door
Strike for
Wood Frames
4-1/8" H
1" W
1-1/4" D



RY-ES

External
Signaling
Relay
4-1/8" H
2-7/16" W
1-5/8" D



IER-2

Call
Extension
Speaker
4-3/4" H
3-7/16" W
1-1/8" D



MCW-S/B

Desk Stand for
DB-1MD or DB-1SD
(mounting hardware
included)
6-1/2" H
6-1/2" W
8" D

Combine this intercom system with our AC Series access control solution for more security benefits!



Specifications

Power Source	15V AC—use PT-1211CA (requires one per tenant master station and one per two tenant sub stations)
Communication	Hands-free (VOX) or push-to-talk (simplex)
Door Release	9.5–20V AC, 70Ω or higher resistance—use EL-12S
Wire Type	<p>Entrance Station to Tenant Master Station: 2-cond., low cap, PE insulation, solid, non-shielded—use Aiphone #871802</p> <p>Tenant Master Station to Tenant Sub Station: 4-cond., low cap, PE insulation, solid, non-shielded—use Aiphone #871804</p> <p>Between Tenant Sub Stations: 4-cond. + 2-cond. when sharing power—use Aiphone #822206 or #871804</p> <p>Power Supply to Tenant Station: 2-cond., low cap, PE insulation, solid, non-shielded—use Aiphone #871802</p>
Distance	<p>Power Supply to Entrance Station or Door Strike (cumulative): 360' (22 AWG) 1,020' (18 AWG)</p> <p>Power Supply to Tenant Station: 180' (22 AWG) 510' (18 AWG)</p> <p>Tenant Master Station to farthest Tenant Sub Station: 330'</p>

